



US 20240251583A1

(19) **United States**

(12) **Patent Application Publication**
Lee et al.

(10) **Pub. No.: US 2024/0251583 A1**

(43) **Pub. Date:** **Jul. 25, 2024**

(54) **LIGHT-EMITTING DEVICE AND ELECTRONIC APPARATUS INCLUDING THE SAME**

(71) Applicant: **Samsung Electronics Co., Ltd.**, Suwon-si (KR)

(72) Inventors: **Sunghun Lee**, Suwon-si (KR); **Byungjoon Kang**, Suwon-si (KR); **Seungyeon Kwak**, Suwon-si (KR); **Sungmin Kim**, Suwon-si (KR); **Hyungjun Kim**, Suwon-si (KR); **Minhan Lee**, Suwon-si (KR); **Hongsoo Lee**, Suwon-si (KR); **Kyuyoung Hwang**, Suwon-si (KR)

(21) Appl. No.: **18/390,377**

(22) Filed: **Dec. 20, 2023**

(30) **Foreign Application Priority Data**

Dec. 30, 2022 (KR) 10-2022-0191045

Publication Classification

(51) **Int. Cl.**
H10K 50/12 (2006.01)
C09K 11/06 (2006.01)
H10K 50/16 (2006.01)

H10K 85/30 (2006.01)
H10K 85/60 (2006.01)
(52) **U.S. Cl.**
CPC **H10K 50/121** (2023.02); **C09K 11/06** (2013.01); **H10K 50/16** (2023.02); **H10K 85/342** (2023.02); **H10K 85/346** (2023.02); **H10K 85/6572** (2023.02); **H10K 85/658** (2023.02); **H10K 2101/90** (2023.02)

(57) **ABSTRACT**

A light-emitting device and an electronic apparatus including the light-emitting device. The light-emitting device includes a first electrode, a second electrode, and an interlayer arranged between the first electrode and the second electrode, the interlayer includes an emission layer, the emission layer includes one or more m1 hosts, a sensitizer, and a fluorescent emitter, where m1 is an integer of 1 or more, and when m1 is 2 or more, the two or more hosts are each different from the other, the one or more m1 hosts, the sensitizer, and the fluorescent emitter are different from each other, and Expression 1 is satisfied.

$0 \text{ debye} \leq |PDM(S) - PDM(H)| \leq 3 \text{ debye}$ Expression 1

Expression 1 is the same as described in the present specification.

101

190
170
150
120
110