



US 20240237237A1

(19) **United States**

(12) **Patent Application Publication**
YAN et al.

(10) **Pub. No.: US 2024/0237237 A1**

(43) **Pub. Date: Jul. 11, 2024**

(54) **ELECTRONIC DEVICE**

Publication Classification

(71) Applicant: **Honor Device Co., Ltd.**, Shenzhen (CN)

(51) **Int. Cl.**
H05K 5/02 (2006.01)
G06F 1/16 (2006.01)
H05K 5/00 (2006.01)

(72) Inventors: **Bin YAN**, Shenzhen (CN); **Guotong ZHOU**, Shenzhen (CN); **Dong MA**, Shenzhen (CN)

(52) **U.S. Cl.**
CPC **H05K 5/0217** (2013.01); **G06F 1/1641** (2013.01); **H05K 5/0086** (2013.01); **H05K 5/0247** (2013.01)

(73) Assignee: **Honor Device Co., Ltd.**, Shenzhen (CN)

(57) **ABSTRACT**

(21) Appl. No.: **17/795,100**

An electronic device has a middle frame with a middle frame hole. A screen chip and a screen outlet line are located on a first side of the middle frame, a battery is located on a second side of the middle frame, and the screen chip is laminated to a large surface of the screen outlet line. To avoid contact between the middle frame and the screen chip, the middle frame hole accommodates the screen chip, a protruding height of the screen chip relative to the large surface of the screen outlet line is less than a thickness of the middle frame hole, and a distance between the screen chip and the battery is greater than an avoidance distance of the screen chip. The screen chip is prevented from moving downward to be in contact with the middle frame when a user presses the display, thereby avoiding damage.

(22) PCT Filed: **Apr. 21, 2022**

(86) PCT No.: **PCT/CN2022/088272**

§ 371 (c)(1),
(2) Date: **Jul. 25, 2022**

(30) **Foreign Application Priority Data**

Aug. 2, 2021 (CN) 202110878914.8

