US 20240214453A1

(19) **United States**

(12) **Patent Application Publication** (10) **Pub. No.: US 2024/0214453 A1**

HSU et al. (43) **Pub. Date: Jun. 27, 2024**

(54) **SMART CONTROL MODULE FOR COIN-OPERATED DEVICE**

(71) Applicant: **CHUNG-HAO HSU**, Taipei City (TW)

(72) Inventors: **Chung-Hao HSU**, Taipei City (TW); **SAN-FENG HUANG**, Taipei City (TW)

(73) Assignee: **CHUNG-HAO HSU**, Taipei City (TW)

(21) Appl. No.: **18/394,921**

(22) Filed: **Dec. 22, 2023**

(30) **Foreign Application Priority Data**

Dec. 23, 2022 (TW) 111149636

Publication Classification

(51) **Int. Cl.**
H04L 67/125 (2006.01)
G06Q 30/015 (2006.01)

(52) **U.S. Cl.**
CPC ***H04L 67/125*** (2013.01); ***G06Q 30/015*** (2023.01)

(57) **ABSTRACT**

A smart control module for a coin-operated device includes a control board disposed with a processing unit, a back-end port, and a communication unit that are electrically connected to the processing unit. A front-end port is disposed on the control board and is adapted to receive a coin insertion signal outputted by a coin acceptor. The back-end port outputs the coin insertion signal in a bypassing way. When the communication unit receives a control signal from a service platform, the processing unit outputs a simulated coin insertion signal through the back-end port. Upon using the present invention, the front-end port and the back-end port are connected between the coin acceptor and a controller of the coin-operated device. The service platform could remotely control the back-end port to output the simulated coin insertion signal to the controller after receiving a malfunction reported by a user.