



US 20230232672A1

(19) **United States**
(12) **Patent Application Publication** (10) **Pub. No.: US 2023/0232672 A1**
SUN et al. (43) **Pub. Date: Jul. 20, 2023**

(54) **DISPLAY SUBSTRATE, METHOD FOR MANUFACTURING THE SAME AND DISPLAY DEVICE**

Publication Classification

(71) Applicants: **CHENGDU BOE OPTOELECTRONICS TECHNOLOGY CO., LTD.**, Chengdu (CN); **BOE TECHNOLOGY GROUP CO., LTD.**, Beijing (CN)

(51) **Int. Cl.**
H01L 51/00 (2006.01)
G01J 1/42 (2006.01)
G06V 40/13 (2022.01)
G01S 17/08 (2006.01)
G06V 40/16 (2022.01)

(72) Inventors: **Kuo SUN**, Beijing (CN); **Yang WANG**, Beijing (CN); **Mingche HSIEH**, Beijing (CN); **Haijun YIN**, Beijing (CN)

(52) **U.S. Cl.**
CPC *H10K 59/126* (2023.02); *G01J 1/4204* (2013.01); *G01S 17/08* (2013.01); *G06V 40/16* (2022.01); *G06V 40/1318* (2022.01); *H10K 59/65* (2023.02); *H10K 71/00* (2023.02); *H10K 59/1201* (2023.02)

(73) Assignees: **CHENGDU BOE OPTOELECTRONICS TECHNOLOGY CO., LTD.**, Chengdu (CN); **BOE TECHNOLOGY GROUP CO., LTD.**, Beijing (CN)

(57) **ABSTRACT**

(21) Appl. No.: **18/180,727**

(22) Filed: **Mar. 8, 2023**

Related U.S. Application Data

(63) Continuation-in-part of application No. 16/346,435, filed as application No. PCT/CN2018/103145 on Aug. 30, 2018.

(30) **Foreign Application Priority Data**

Jan. 12, 2018 (CN) 201810031285.3

A display substrate, a method for manufacturing the same and a display device are provided. The display substrate includes a base substrate and a thin film transistor array arranged on the base substrate. Multiple pixels arranged in an array are provided in an effective display region of the display substrate. The effective display region includes an optical element arrangement region and other display regions, and a transmittance of the optical element arrangement region is larger than transmittances of the other display regions. In the optical element arrangement region, an optical element is arranged on a side of the base substrate away from the thin film transistor array, and the optical element emits and receives light that is transmitted through the display substrate.

