

(19) United States

(12) Patent Application Publication (10) Pub. No.: US 2022/0369439 A1 Zou et al.

Nov. 17, 2022 (43) Pub. Date:

(54) DRIVER FOR LED DEVICE, LED SYSTEM, AND ADAPTATION METHOD FOR LED DEVICE

(52) U.S. Cl. CPC H05B 45/37 (2020.01); H05B 45/345 (2020.01); **H05B** 45/305 (2020.01)

(71) Applicant: CURRENT LIGHTING

SOLUTIONS, LLC, East Cleveland,

OH (US)

(72) Inventors: Qiang Zou, Xian, ShaanXi (CN);

Zhichao Liu, Shanghai (CN); Qi Yan,

Xian, ShaanXi (CN)

(21) Appl. No.: 17/761,258

PCT Filed: Sep. 17, 2019 (22)

PCT/CN2019/106175 (86) PCT No.:

§ 371 (c)(1),

(2) Date: Mar. 17, 2022

Publication Classification

(51) Int. Cl. H05B 45/37 (2006.01)H05B 45/345 (2006.01)H05B 45/305 (2006.01)

(57)ABSTRACT

A driver for a light-emitting diode (LED) device comprises: a rectifier, a current regulator and a detecting module. The rectifier is coupled to a ballast and configured to convert an alternating current from the ballast into a direct current. The current regulator is coupled between the rectifier and the LED device, and configured to receive the direct current from the rectifier and output a driving current to the LED device. The detecting module is configured to detect a signal indicating an output characteristic of the ballast, during a startup stage of the LED device. The current regulator is configured to convert the direct current from the rectifier into the driving current with a value equal to or less than a preset current threshold when the signal meets a preset condition, and the preset current threshold is less than a maximum current the LED device is able to carry without damage.

