US 20240215430A1

(19) United States

(12) Patent Application Publication (10) Pub. No.: US 2024/0215430 A1

LIU et al. (43) Pub. Date: Jun. 27, 2024

(54) **STRETCHABLE DISPLAY SUBSTRATE AND MANUFACTURING METHOD THEREOF**

(71) Applicant: **BOE Technology Group Co., Ltd.**, Beijing (CN)

(72) Inventors: **Wenqi LIU**, Beijing (CN); **Jinxiang XUE**, Beijing (CN); **Wei QUAN**, Beijing (CN); **Qingyu HUANG**, Beijing (CN); **Jingkai NI**, Beijing (CN)

(21) Appl. No.: **17/799,807**

(22) PCT Filed: **Nov. 10, 2021**

(86) PCT No.: **PCT/CN2021/129771**

§ 371 (c)(1),
(2) Date: **Aug. 15, 2022**

(30) **Foreign Application Priority Data**

Feb. 26, 2021 (CN) 202110219236.4

Publication Classification

(51) **Int. Cl.**

H10K 77/10	(2006.01)
H10K 59/12	(2006.01)
H10K 59/127	(2006.01)
H10K 59/131	(2006.01)
H10K 59/80	(2006.01)
H10K 71/80	(2006.01)
H10K 102/00	(2006.01)

(52) **U.S. Cl.**

CPC ***H10K 77/111*** (2023.02); ***H10K 59/1201*** (2023.02); ***H10K 59/127*** (2023.02); ***H10K 59/131*** (2023.02); ***H10K 59/873*** (2023.02); ***H10K 71/80*** (2023.02); *H10K 2102/311* (2023.02)

(57) **ABSTRACT**

The present disclosure provides a stretchable display substrate and a manufacturing method. The stretchable display substrate includes: a base substrate, a plurality of opening patterns being distributed on the base substrate, a plurality of bridges being formed between adjacent ones of at least a part of opening patterns in the plurality of opening patterns to define islands; a plurality of display units, at least one display unit being arranged on each island; a plurality of wiring units each coupled between the display units on the islands and arranged on the bridge; and a thin film encapsulation layer including a first encapsulation portion covering a side of each display unit away from the base substrate and a second encapsulation portion at least covering a side of each display unit adjacent to the opening pattern. Each of at least a part of opening patterns has different opening sizes at a side of the base substrate adjacent to the display unit and a side of the base substrate away from the display unit, and the opening pattern has at least one step-like structure at a side adjacent to the island. According to the present disclosure, it is able to improve the reliability of a display element.