

(19) United States

(12) Patent Application Publication (10) Pub. No.: US 2024/0213478 A1 Lee et al.

Jun. 27, 2024 (43) Pub. Date:

(54) NEGATIVE ELECTRODE FOR SECONDARY BATTERY AND MANUFACTURING METHOD THEREOF

(71) Applicant: **SK On Co., Ltd.**, Seoul (KR)

Inventors: Dong Hoon Lee, Daejeon (KR); Ju Hyun Kim, Daejeon (KR)

Appl. No.: 18/393,858

(22)Filed: Dec. 22, 2023

(30)Foreign Application Priority Data

Dec. 26, 2022 (KR) 10-2022-0184766

Publication Classification

(51)	Int. Cl.	
	H01M 4/62	(2006.01)
	H01M 4/04	(2006.01)
	H01M 4/133	(2006.01)
	H01M 4/134	(2006.01)

H01M 4/1393	(2006.01)
H01M 4/1395	(2006.01)
H01M 4/38	(2006.01)
H01M 4/587	(2006.01)

(52) U.S. Cl.

CPC H01M 4/622 (2013.01); H01M 4/0404 (2013.01); H01M 4/133 (2013.01); H01M 4/134 (2013.01); H01M 4/1393 (2013.01); H01M 4/1395 (2013.01); H01M 4/386 (2013.01); H01M 4/587 (2013.01); H01M 2004/027 (2013.01)

(57)ABSTRACT

An anode for secondary battery including an anode current collector; a first layer including a binder and contacting at least one cross-section of the anode current collector in a thickness direction; and a second layer including an anode active material and contacting one cross-section of the first layer in a thickness direction. An end portion of the first layer in a width direction perpendicular to the thickness direction protrudes more than an end portion of the second layer in a width direction.

1000

