

(19) United States

(12) Patent Application Publication (10) Pub. No.: US 2024/0213185 A1 Jogalekar et al.

Jun. 27, 2024 (43) **Pub. Date:**

(54) SYSTEM, ELECTRONIC DEVICE AND PACKAGE WITH VERTICAL TO HORIZONTAL SUBSTRATE INTEGRATED WAVEGUIDE TRANSITION AND HORIZONTAL GROUNDED COPLANAR WAVEGUIDE TRANSITION

(71) Applicant: Texas Instruments Incorporated, Dallas, TX (US)

(72) Inventors: Aditya Nitin Jogalekar, Dallas, TX (US); Harshpreet Singh Phull Bakshi, Dallas, TX (US); Rajen Manicon Murugan, Dallas, TX (US); Sylvester Ankamah-Kusi, Dallas, TX (US)

(21) Appl. No.: 18/146,886

(22) Filed: Dec. 27, 2022

Publication Classification

(51)	Int. Cl.	
` ′	H01L 23/66	(2006.01)
	H01L 21/48	(2006.01)
	H01L 21/56	(2006.01)
	H01L 23/31	(2006.01)

H01L 23/498	(2006.01)
H01P 3/00	(2006.01)
H01P 3/12	(2006.01)
H01P 5/107	(2006.01)
H01P 11/00	(2006.01)

(52) U.S. Cl. CPC H01L 23/66 (2013.01); H01L 21/4853 (2013.01); H01L 21/4857 (2013.01); H01L 21/565 (2013.01); H01L 23/3121 (2013.01); H01L 23/49822 (2013.01); H01L 23/49838 (2013.01); H01P 3/003 (2013.01); H01P 3/121 (2013.01); H01P 5/107 (2013.01); H01P 11/002 (2013.01); H01P 11/003 (2013.01); H01L 2223/6633 (2013.01)

ABSTRACT (57)

An electronic device includes a multilevel package substrate with a horizontal substrate integrated waveguide (SIW) with a channel, a vertical SIW with an opening, a grounded coplanar waveguide (GCPW), a first transition between the horizontal SIW and the GCPW, and a second transition between the horizontal and vertical SIWs, as well as a semiconductor die having conductive structures coupled to a signal trace and a ground trace of the GCPW, and a package structure that encloses the semiconductor die and a portion of the multilevel package substrate.

