



US 20240237501A9

(19) **United States**
(12) **Patent Application Publication**
LEE et al.

(10) **Pub. No.: US 2024/0237501 A9**
(48) **Pub. Date: Jul. 11, 2024**
CORRECTED PUBLICATION

(54) **DISPLAY DEVICE AND MANUFACTURING METHOD THEREOF**

Publication Classification

(71) Applicant: **Samsung Display Co., LTD.**,
Yongin-si, Gyeonggi-do (KR)
(72) Inventors: **Jae Hun LEE**, Yongin-si (KR); **Kab Jong SEO**, Yongin-si (KR); **Jun Ho SIM**, Yongin-si (KR); **Yang-Ho JUNG**,
Yongin-si (KR)
(73) Assignee: **Samsung Display Co., LTD.**,
Yongin-si, Gyeonggi-do (KR)

(51) **Int. Cl.**
H10K 59/80 (2006.01)
H10K 59/122 (2006.01)
H10K 71/16 (2006.01)
H10K 71/20 (2006.01)
(52) **U.S. Cl.**
CPC **H10K 59/8792** (2023.02); **H10K 59/122**
(2023.02); **H10K 71/166** (2023.02); **H10K**
71/231 (2023.02)

(21) Appl. No.: **18/326,116**
(22) Filed: **May 31, 2023**

(57) **ABSTRACT**

Prior Publication Data

(15) Correction of US 2024/0138243 A1 Apr. 25, 2024
See (22) Filed
See (30) Foreign Application Data

(65) US 2024/0138243 A1 Apr. 25, 2024

Foreign Application Priority Data

Oct. 24, 2022 (KR) 10-2022-0137369

A display device according to an embodiment includes a light-emitting device disposed on a substrate and including an emission layer, and a light control layer disposed on the light-emitting device. The light control layer includes a plurality of light blocking patterns extending in a first direction and spaced in a second direction intersecting the first direction, and a transmission layer disposed among the plurality of light blocking patterns and including a transparent organic layer and a transparent inorganic layer that are alternately stacked on each other.

