

(19) United States

(12) Patent Application Publication (10) Pub. No.: US 2023/0231487 A1 KUSUKAWA et al.

Jul. 20, 2023 (43) **Pub. Date:**

(54) SEMICONDUCTOR DEVICE, BUSBAR, AND **POWER CONVERTER**

(71) Applicant: Hitachi Astemo, Ltd., Hitachinaka-shi,

Ibaraki (JP)

Inventors: Junpei KUSUKAWA, Tokyo (JP);

Masahito MOCHIZUKI, Tokyo (JP);

Eiichi IDE, Tokyo (JP)

Assignee: Hitachi Astemo, Ltd., Hitachinaka-shi,

Ibaraki (JP)

Appl. No.: (21)17/924,569

PCT Filed: Jan. 22, 2021

(86) PCT No.: PCT/JP2021/002145

§ 371 (c)(1),

Nov. 10, 2022 (2) Date:

(30)Foreign Application Priority Data

(JP) 2020-084711

Publication Classification

(51)	Int. Cl.	
	H02M 7/00	(2006.01)
	H01L 25/07	(2006.01)
	H01L 23/049	(2006.01)
	H01L 23/00	(2006.01)

(52) U.S. Cl.

CPC H02M 7/003 (2013.01); H01L 25/072 (2013.01); H01L 23/049 (2013.01); H01L 24/48 (2013.01); H01L 2924/30107 (2013.01); H01L 2924/13055 (2013.01); H01L *2224/48137* (2013.01)

ABSTRACT (57)

Provided are a semiconductor device, a busbar, and a power converter that can suppress an increase in the size of the device and in inductance while ensuring insulation performance between terminals. For example, a semiconductor device 1 includes a first terminal 110 projecting from a sealing body 100 along a given direction, and a second terminal 120 adjacent to the first terminal 110 with a space formed between the second terminal 120 and the first terminal 110, the second terminal 120 projecting from the sealing body 100 along a given direction in a direction of projection that is the same as a direction of projection of the first terminal 110. The first terminal 110 has a first exposed part 112 exposed outside the sealing body 100. The second terminal 120 has a second sheathed part 121 projecting from the sealing body 100, the second sheathed part 121 being sheathed with an insulating material, and a second exposed part 122 projecting from the second sheathed part 121, the second exposed part 122 being exposed outside the sealing body 100. A distance D2 along a given direction from a front end 121a of the second sheathed part 121 to the sealing body 100 is longer than a distance D1 along the given direction from a front end 112a of the first exposed part 112 to the sealing body 100.

