US 20240215291A1

(19) United States

(12) Patent Application Publication (10) Pub. No.: US 2024/0215291 A1

SASAGAWA et al. (43) Pub. Date: Jun. 27, 2024

(54) **DISPLAY DEVICE AND METHOD FOR MANUFACTURING THE DISPLAY DEVICE**

(71) Applicant: **SEMICONDUCTOR ENERGY LABORATORY CO., LTD.**, Atsugi-shi, Kanagawa-Ken (JP)

(72) Inventors: **Shinya SASAGAWA**, Chigasaki, Kanagawa (JP); **Ryota HODO**, Atsugi, Kanagawa (JP); **Hiroaki HONDA**, Odawara, Kanagawa (JP); **Yasunori SASAMURA**, Hiratsuka, Kanagawa (JP)

(21) Appl. No.: **18/555,927**

(22) PCT Filed: **Apr. 11, 2022**

(86) PCT No.: **PCT/IB2022/053349**

§ 371 (c)(1),
(2) Date: **Oct. 18, 2023**

(30) **Foreign Application Priority Data**

Apr. 23, 2021 (JP) 2021-073256

Publication Classification

(51) **Int. Cl.**

H10K 50/13	(2006.01)
H10K 59/131	(2006.01)
H10K 71/00	(2006.01)
H10K 71/40	(2006.01)
H10K 71/60	(2006.01)

(52) **U.S. Cl.**

CPC ***H10K 50/13*** (2023.02); ***H10K 59/131*** (2023.02); ***H10K 71/40*** (2023.02); ***H10K 71/60*** (2023.02); ***H10K 71/621*** (2023.02)

(57) **ABSTRACT**

Provided is a display device with high display quality. The display device includes a first pixel and a second pixel provided to be adjacent to the first pixel. The first pixel includes a first pixel electrode, a first EL layer over the first pixel electrode, and a common electrode over the first EL layer; the second pixel includes a second pixel electrode, a second EL layer over the second pixel electrode, and the common electrode over the second EL layer; each of the first pixel electrode and the second pixel electrode has a tapered shape on a side surface; a taper angle of the tapered shape is smaller than 90 degrees; and the display device includes a region where the distance between the first pixel electrode and the second pixel electrode is less than or equal to one micrometer.