US 20240251590A1

(19) **United States**

(12) **Patent Application Publication** (10) **Pub. No.: US 2024/0251590 A1**

**Ishizuya et al.** (43) **Pub. Date: Jul. 25, 2024**

(54) **LIGHT-EMITTING DEVICE, DISPLAY DEVICE, IMAGING DEVICE, ELECTRONIC DEVICE, AND METHOD FOR PRODUCING LIGHT-EMITTING DEVICE**

(71) Applicant: **CANON KABUSHIKI KAISHA**, Tokyo (JP)

(72) Inventors: **Koji Ishizuya**, Kanagawa (JP); **Hiroaki Sano**, Kanagawa (JP)

(21) Appl. No.: **18/626,593**

(22) Filed: **Apr. 4, 2024**

**Related U.S. Application Data**

(63) Continuation of application No. 17/506,952, filed on Oct. 21, 2021, now Pat. No. 11,980,053.

(30) **Foreign Application Priority Data**

Oct. 28, 2020 (JP) ..... 2020-180655

**Publication Classification**

(51) **Int. Cl.**

| | |
|---|---|
| ***H10K 50/856*** | (2006.01) |
| ***H10K 50/844*** | (2006.01) |
| ***H10K 50/852*** | (2006.01) |
| ***H10K 50/858*** | (2006.01) |
| ***H10K 50/86*** | (2006.01) |
| ***H10K 59/38*** | (2006.01) |
| ***H10K 59/88*** | (2006.01) |
| ***H10K 71/00*** | (2006.01) |
| ***H10K 102/00*** | (2006.01) |

(52) **U.S. Cl.**

CPC ..... ***H10K 50/856*** (2023.02); ***H10K 50/844*** (2023.02); ***H10K 50/852*** (2023.02); ***H10K 50/86*** (2023.02); ***H10K 50/865*** (2023.02); ***H10K 71/00*** (2023.02); *H10K 50/858* (2023.02); *H10K 59/38* (2023.02); *H10K 59/88* (2023.02); *H10K 2102/3026* (2023.02); *H10K 2102/351* (2023.02)

(57) **ABSTRACT**

The light-emitting device has: a display region; a peripheral region; a first light-emitting element having a light-emitting region in which a lower electrode, a light-emitting layer, and an upper electrode are laminated; a first laminated section, between the substrate and the lower electrode of the first light-emitting element, in which there are laminated a first high-reflection layer and a first low-reflection layer that has a lower reflectance than the first high-reflection layer; a peripheral laminated section, in the peripheral region, in which there are laminated on the substrate; a peripheral lamination layer in which a peripheral high-reflection layer and a peripheral low-reflection layer that has a lower reflectance than the peripheral high-reflection layer are laminated. For at least a portion of the first laminated section that overlaps in plan view with the light-emitting region, the first low-reflection layer has an opening such that the first high-reflection layer is exposed.