



US 20240215159A1

(19) **United States**(12) **Patent Application Publication**

Lee et al.

(10) **Pub. No.: US 2024/0215159 A1**(43) **Pub. Date: Jun. 27, 2024**(54) **CIRCUIT BOARD AND MANUFACTURING METHOD THEREOF****Publication Classification**(71) Applicant: **SAMSUNG ELECTRO-MECHANICS CO., LTD.**,
Suwon-si (KR)(72) Inventors: **Sang-min Lee**, Suwon-si (KR); **Youngil Cho**, Suwon-si (KR)(73) Assignee: **SAMSUNG ELECTRO-MECHANICS CO., LTD.**,
Suwon-si (KR)(51) **Int. Cl.****H05K 1/03** (2006.01)**H05K 1/11** (2006.01)**H05K 3/00** (2006.01)**H05K 3/10** (2006.01)(52) **U.S. Cl.**CPC **H05K 1/0353** (2013.01); **H05K 1/111**(2013.01); **H05K 1/115** (2013.01); **H05K****3/0017** (2013.01); **H05K 3/103** (2013.01);**H05K 2201/0939** (2013.01); **H05K 2201/099**

(2013.01)

(21) Appl. No.: **18/131,019**(22) Filed: **Apr. 5, 2023**(30) **Foreign Application Priority Data**

Dec. 26, 2022 (KR) 10-2022-0184350

(57)

ABSTRACT

A circuit board according to an embodiment includes: a first insulating layer that does not include a reinforcing material; a conductive pad that protrudes above a surface of the first insulating layer, and a second insulating layer that is disposed below the first insulating layer and includes a reinforcing material. A corner of the conductive pad has a curved shape.

