

(19) **United States**(12) **Patent Application Publication**  
**Chao et al.**(10) **Pub. No.: US 2023/0231560 A1**(43) **Pub. Date: Jul. 20, 2023**(54) **METHOD FOR PERFORMING  
DIVIDED-CLOCK PHASE  
SYNCHRONIZATION IN  
MULTI-DIVIDED-CLOCK SYSTEM,  
SYNCHRONIZATION CONTROL CIRCUIT,  
SYNCHRONIZATION CONTROL  
SUB-CIRCUIT, AND ELECTRONIC DEVICE****Publication Classification**

(51) **Int. Cl.**  
*H03L 7/00* (2006.01)  
*H03K 19/21* (2006.01)  
*H03K 21/02* (2006.01)  
*G11C 11/4076* (2006.01)  
(52) **U.S. Cl.**  
CPC ..... *H03L 7/00* (2013.01); *H03K 19/21*  
(2013.01); *H03K 21/023* (2013.01); *G11C*  
*11/4076* (2013.01)

(71) Applicant: **Faraday Technology Corp.**, Hsin-Chu  
City (TW)(72) Inventors: **Ko-Ching Chao**, Hsin-Chu City (TW);  
**Chih-Hung Wu**, Hsin-Chu City (TW);  
**Po-Wen Hsiao**, Hsin-Chu City (TW);  
**Zhou-Lun Liou**, Hsin-Chu City (TW)(73) Assignee: **Faraday Technology Corp.**, Hsin-Chu  
City (TW)(21) Appl. No.: **17/974,532**(22) Filed: **Oct. 27, 2022**(30) **Foreign Application Priority Data**

Jan. 14, 2022 (TW) ..... 111101630

(57) **ABSTRACT**

A method for performing divided-clock phase synchronization in a multi-divided-clock system, an associated synchronization control circuit, an associated synchronization control sub-circuit and an associated electronic device are provided. The method may include: performing frequency division operations according to a source clock to generate a first divided clock and a second divided clock; performing phase relationship detection on the first divided clock according to the second divided clock to generate a phase relationship detection result signal; performing a logic operation on a first phase selection result output signal and the phase relationship detection result signal to generate a second phase selection result output signal; and outputting one of the second divided clock and an inverted signal of the second divided clock according to the second phase selection result output signal, for further use in a physical layer circuit.

