

(19) United States

(12) Patent Application Publication (10) Pub. No.: US 2024/0213024 A1 Khan

Jun. 27, 2024 (43) **Pub. Date:**

(54) DIAMOND SEMICONDUCTOR SYSTEM AND **METHOD**

- (71) Applicant: AKHAN Semiconductor, Inc., Gurnee, IL (US)
- Inventor: Adam Khan, Tiburon, CA (US)
- (21) Appl. No.: 18/418,976
- (22) Filed: Jan. 22, 2024

Related U.S. Application Data

- (60) Continuation of application No. 18/167,011, filed on Feb. 9, 2023, now Pat. No. 11,915,934, which is a continuation of application No. 17/329,035, filed on May 24, 2021, now Pat. No. 11,605,541, which is a continuation of application No. 16/052,575, filed on Aug. 1, 2018, now Pat. No. 11,043,382, which is a continuation of application No. 15/287,692, filed on Oct. 6, 2016, now abandoned, which is a division of application No. 13/725,978, filed on Dec. 21, 2012, now Pat. No. 8,933,462, which is a continuation of application No. 14/595,320, filed on Jan. 13, 2015, now abandoned.
- (60) Provisional application No. 61/578,364, filed on Dec. 21, 2011, provisional application No. 61/578,371, filed on Dec. 21, 2011.

Publication Classification

(51)	Int. Cl.	
` ′	H01L 21/04	(2006.01)
	H01L 21/02	(2006.01)
	H01L 21/285	(2006.01)
	H01L 21/324	(2006.01)
	H01L 21/768	(2006.01)
	H01L 29/16	(2006.01)
	H01L 29/36	(2006.01)
	H01L 29/66	(2006.01)
	H01L 29/868	(2006.01)

(52) U.S. Cl.

CPC H01L 21/043 (2013.01); H01L 21/02425 (2013.01); H01L 21/02527 (2013.01); H01L 21/0415 (2013.01); H01L 21/042 (2013.01); H01L 21/0435 (2013.01); H01L 21/2855 (2013.01); H01L 21/28556 (2013.01); H01L 21/324 (2013.01); H01L 21/76871 (2013.01); H01L 29/1602 (2013.01); H01L 29/36 (2013.01); H01L 29/6603 (2013.01); H01L 29/868 (2013.01)

(57)**ABSTRACT**

Disclosed herein is a new and improved system and method for fabricating diamond semiconductors. The method may include the steps of selecting a diamond semiconductor material having a surface, exposing the surface to a source gas in an etching chamber, forming a carbide interface contact layer on the surface; and forming a metal layer on the interface layer.

