



US 20240215339A1

(19) **United States**

(12) **Patent Application Publication**
SUGITANI et al.

(10) **Pub. No.: US 2024/0215339 A1**

(43) **Pub. Date: Jun. 27, 2024**

(54) **DISPLAY DEVICE AND METHOD OF
MANUFACTURING THE SAME**

H10K 59/123 (2006.01)

H10K 59/131 (2006.01)

(71) Applicant: **Samsung Display Co., LTD.**, Yongin-si
(KR)

(52) **U.S. Cl.**

CPC **H10K 59/124** (2023.02); **H10K 59/1201**
(2023.02); **H10K 59/123** (2023.02); **H10K**
59/131 (2023.02); **H10K 71/621** (2023.02)

(72) Inventors: **KOICHI SUGITANI**, Yongin-si (KR);
GWUI-HYUN PARK, Yongin-si (KR);
HOKYUNG JANG, Yongin-si (KR);
SAEHEE HAN, Yongin-si (KR)

(57)

ABSTRACT

(73) Assignee: **Samsung Display Co., LTD.**, Yongin-si
(KR)

(21) Appl. No.: **18/455,666**

(22) Filed: **Aug. 25, 2023**

(30) **Foreign Application Priority Data**

Dec. 22, 2022 (KR) 10-2022-0181684

Publication Classification

(51) **Int. Cl.**

H10K 59/124 (2006.01)

H10K 59/12 (2006.01)

A display device includes a light emitting area and a non-light emitting area adjacent to the light emitting area, a first conductive layer disposed on a substrate in the light emitting area and the non-light emitting area, a second conductive layer disposed on the first conductive layer in the light emitting area, a first insulating film disposed on the first conductive layer, overlapping the first conductive layer and the second conductive layer in the light emitting area, and having a first permittivity, and a second insulating film disposed between the first insulating film and the second conductive layer, disposed in the light emitting area and the non-light emitting area, overlapping the first insulating film and the first conductive layer, and having a second permittivity greater than the first permittivity.

