



US 20220360201A1

(19) **United States**(12) **Patent Application Publication** (10) **Pub. No.: US 2022/0360201 A1**
(43) **Pub. Date: Nov. 10, 2022**(54) **CONTROL DEVICE, CONVEYANCE
DEVICE, ELECTRIC CYLINDER, AND
STORAGE MEDIUM**(30) **Foreign Application Priority Data**

Mar. 5, 2020 (JP) PCT/JP2020/009469

(71) Applicant: **HIRATA CORPORATION,**
Kumamoto-shi (JP)**Publication Classification**(72) Inventors: **Naoto ARITA,** Kumamoto-shi (JP);
Satoshi NISHIMOTO, Kumamoto-shi
(JP); **Koichi NAKANO,** Kumamoto-shi
(JP)(51) **Int. Cl.**
H02P 6/30 (2006.01)
B65G 13/06 (2006.01)
H02P 6/20 (2006.01)
H02P 6/08 (2006.01)
(52) **U.S. Cl.**
CPC **H02P 6/30** (2016.02); **B65G 13/06**
(2013.01); **H02P 6/20** (2013.01); **H02P 6/08**
(2013.01); **B65G 2203/0291** (2013.01)(21) Appl. No.: **17/848,817**(57) **ABSTRACT**(22) Filed: **Jun. 24, 2022****Related U.S. Application Data**(63) Continuation of application No. PCT/JP2021/
005007, filed on Feb. 10, 2021.

A control device includes first and second input terminals to which a DC voltage for driving a motor is input, and a control unit. The control unit sets a rotation direction of the motor based on first input to the first input terminal or the second input terminal. A rotation speed of the motor is changed based on a subsequence input of the DC voltage.

