



US 20240237185A1

(19) **United States**

(12) **Patent Application Publication**
ZHENG et al.

(10) **Pub. No.: US 2024/0237185 A1**

(43) **Pub. Date: Jul. 11, 2024**

(54) **HIGH-TEMPERATURE SUPERCONDUCTING PLASMA THRUSTER SYSTEM HAVING VARIABLE TEMPERATURE RANGES AND BEING APPLIED IN SPACE**

F03H 1/00 (2006.01)

H05H 1/54 (2006.01)

(52) **U.S. Cl.**

CPC **H05H 1/28** (2013.01); **B64G 1/413**

(2023.08); **F03H 1/0031** (2013.01); **H05H**

1/54 (2013.01); **H05H 2242/10** (2013.01)

(71) Applicant: **HEFEI INSTITUTES OF PHYSICAL SCIENCE, CHINESE ACADEMY OF SCIENCES, HEFEI (CN)**

(72) Inventors: **JINXING ZHENG, HEFEI (CN); HAIYANG LIU, HEFEI (CN); XIAOLIANG ZHU, HEFEI (CN); YUDONG LU, HEFEI (CN); MING LI, HEFEI (CN); YIFAN DU, HEFEI (CN); LEI ZHU, HEFEI (CN); ZHUOYAO TANG, HEFEI (CN)**

(57)

ABSTRACT

A high-temperature superconducting plasma thruster system, having variable temperature ranges and being applied in space, is provided. The high-temperature superconducting plasma thruster system includes: a cathode-anode assembly, a high-temperature superconducting magnet system, a supporting and adjusting platform, a power-and-gas supply and cooling system, and an obtaining control system. The cathode-anode assembly is disposed at a center of a ring of the high-temperature superconducting magnet system; the cathode-anode assembly and the high-temperature superconducting magnet system are spatially engaged with each other by the supporting and adjusting platform to form a main body of the thruster system; the power-and-gas supply and cooling system and the obtaining control system are located outside of the main body of the thruster system and are connected to the cathode-anode assembly and the high-temperature superconducting magnet system.

(21) Appl. No.: **18/595,325**

(22) Filed: **Mar. 4, 2024**

(30) **Foreign Application Priority Data**

Jan. 10, 2023 (CN) 202310034812.7

Publication Classification

(51) **Int. Cl.**

H05H 1/28 (2006.01)

B64G 1/40 (2006.01)

