



US 20240237250A9

(19) **United States**
(12) **Patent Application Publication**
LIN

(10) **Pub. No.: US 2024/0237250 A9**
(48) **Pub. Date: Jul. 11, 2024**
CORRECTED PUBLICATION

(54) **FPC/FFC TENSION KEEPING DEVICE AND ELECTRONIC APPARATUS HAVING THE SAME**

(71) Applicant: **FOSITEK CORPORATION**, New Taipei City (TW)

(72) Inventor: **Wen-Yen LIN**, New Taipei City (TW)

(73) Assignee: **FOSITEK CORPORATION**, New Taipei City (TW)

(21) Appl. No.: **18/078,674**

(22) Filed: **Dec. 9, 2022**

Prior Publication Data

(15) Correction of US 2024/0138083 A1 Apr. 25, 2024
See (30) Foreign Application Data.

(65) US 2024/0138083 A1 Apr. 25, 2024

(30) **Foreign Application Priority Data**

Oct. 25, 2022 (TW) 111140487

Publication Classification

(51) **Int. Cl.**
H05K 7/14 (2006.01)
G06F 1/16 (2006.01)
H05K 1/02 (2006.01)
(52) **U.S. Cl.**
CPC **H05K 7/1422** (2013.01); **G06F 1/1679**
(2013.01); **G06F 1/1681** (2013.01); **H05K**
1/0277 (2013.01)

(57) **ABSTRACT**

An FPC/FFC tension keeping device is adapted to be mounted to an electronic apparatus, and includes a tension keeping unit that includes a base seat module and a sliding module. The base seat module includes a base seat and two guide members. The base seat has two guiding slots. The guide members are respectively inserted in the guiding slots and fixedly connected to the base seat. The sliding module includes a sliding member and two resilient members. The sliding member is slidably connected to the guide members. The resilient members are respectively disposed in the two guiding slots and are respectively sleeved on the guide members. The resilient members are configured to maintain, during movement of the sliding member, contact between the sliding member and an FPC/FFC board of the electronic apparatus that wraps around the sliding member, and to conserve tension of the FPC/FFC board.

