



US 20240244888A1

(19) **United States**

(12) **Patent Application Publication**  
**TAKAYAMA**

(10) **Pub. No.: US 2024/0244888 A1**

(43) **Pub. Date: Jul. 18, 2024**

(54) **DISPLAY DEVICE AND MANUFACTURING METHOD OF DISPLAY DEVICE**

**Publication Classification**

(51) **Int. Cl.**

**H10K 59/122** (2023.01)

**H10K 59/12** (2023.01)

**H10K 59/80** (2023.01)

(52) **U.S. Cl.**

CPC ..... **H10K 59/122** (2023.02); **H10K 59/1201**

(2023.02); **H10K 59/80521** (2023.02); **H10K**

**59/873** (2023.02)

(71) Applicant: **Japan Display Inc.**, Tokyo (JP)

(72) Inventor: **Masaru TAKAYAMA**, Tokyo (JP)

(73) Assignee: **Japan Display Inc.**, Tokyo (JP)

(21) Appl. No.: **18/420,770**

(22) Filed: **Jan. 24, 2024**

**Related U.S. Application Data**

(63) Continuation of application No. 18/450,412, filed on Aug. 16, 2023, now Pat. No. 11,937,463, which is a continuation of application No. 18/168,584, filed on Feb. 14, 2023.

**Foreign Application Priority Data**

Mar. 10, 2022 (JP) ..... 2022-037169

(57)

**ABSTRACT**

According to one embodiment, a display device includes a substrate, a lower electrode, a rib, a partition including a lower portion and an upper portion, an organic layer provided on the lower electrode and including a light emitting layer, and an upper electrode provided on the organic layer and in contact with the lower portion of the partition. The organic layer includes a first end portion located on the rib, and a second end portion located on the rib on an opposite side of the first end portion. A thickness of the upper electrode immediately above the second end portion is greater than a thickness of the upper electrode immediately above the first end portion.

