

(19) United States

(12) Patent Application Publication (10) Pub. No.: US 2022/0360254 A1 Lee et al.

Nov. 10, 2022 (43) **Pub. Date:**

(54) **LATCH**

(71) Applicant: Taiwan Semiconductor

Manufacturing Company, Ltd.,

Hsinchu (TW)

(72) Inventors: Chia-Fu Lee, Hsinchu (TW);

Hon-Jarn Lin, Hsinchu (TW); Yu-Der

Chih, Hsinchu (TW)

(73) Assignee: Taiwan Semiconductor

Manufacturing Company, Ltd.,

Hsinchu (TW)

(21) Appl. No.: 17/815,322

(22) Filed: Jul. 27, 2022

Related U.S. Application Data

(63) Continuation of application No. 17/162,440, filed on Jan. 29, 2021.

Publication Classification

(51) Int. Cl. H03K 3/356

(2006.01)

U.S. Cl. (52)

CPC *H03K 3/35613* (2013.01)

(57)ABSTRACT

A circuit includes cross coupled invertors including a first invertor and a second inventor. The first invertor and the second invertor are cross coupled at a first data node and a second data node. An input unit is coupled between the cross-coupled invertors and a power node. The input unit controls the cross-coupled invertors in response to a first input signal received at a first input terminal of the input unit and a second input signal received at a second input terminal of the input unit. A first transistor is connected between the power node and a supply node. The first transistor connects the power node to the supply node in response to an enable signal changing to a first value. A second transistor is connected between the power node and ground. The second transistor connects the power node to the ground in response to the enable signal changing to a second value.

