



US 20240178742A1

(19) **United States**(12) **Patent Application Publication**
MIYAJI(10) **Pub. No.: US 2024/0178742 A1**(43) **Pub. Date: May 30, 2024**(54) **POWER CONVERSION DEVICE AND
METHOD FOR CONTROLLING POWER
CONVERSION DEVICE****Publication Classification**

(51) **Int. Cl.**
H02M 1/08 (2006.01)
H02M 7/155 (2006.01)
(52) **U.S. Cl.**
CPC *H02M 1/08* (2013.01); *H02M 7/155*
(2013.01)

(71) Applicant: **Mitsubishi Electric Corporation,**
Tokyo (JP)(72) Inventor: **Yoshitaka MIYAJI,** Tokyo (JP)(73) Assignee: **Mitsubishi Electric Corporation,**
Tokyo (JP)(21) Appl. No.: **18/281,779**(22) PCT Filed: **Dec. 15, 2021**(86) PCT No.: **PCT/JP2021/046198**

§ 371 (c)(1),

(2) Date: **Sep. 13, 2023**(30) **Foreign Application Priority Data**

Apr. 21, 2021 (WO) PCT/JP2021/016128

(57) **ABSTRACT**

A power conversion device includes a semiconductor element, a temperature sensor, a sealing material sealing the semiconductor element, and a driving circuit for the semiconductor element. The temperature sensor measures the temperature of either or both of the semiconductor element and the sealing material. The driving circuit controls a voltage steepness or a voltage crest value to be applied to the semiconductor element, on the basis of temperature information measured by the temperature sensor.

