

(19) United States

(12) Patent Application Publication (10) Pub. No.: US 2023/0232040 A1 LIM et al.

Jul. 20, 2023 (43) **Pub. Date:**

(54) METHOD FOR INTRA PREDICTION AND **DEVICE THEREFOR**

(71) Applicant: LG Electronics Inc., Seoul (KR)

(72) Inventors: Jaehyun LIM, Seoul (KR); Seungwook PARK, Seoul (KR); Yongjoon JEON, Seoul (KR); Jungsun KIM, Seoul (KR); Hendry HENDRY, Seoul (KR); Byeongmoon JEON, Seoul (KR); Joonvoung PARK, Seoul (KR); Chulkeun KIM, Seoul (KR);

Naeri PARK, Seoul (KR)

(21) Appl. No.: 18/125,307

(22) Filed: Mar. 23, 2023

Related U.S. Application Data

- (60)Continuation of application No. 17/190,215, filed on Mar. 2, 2021, which is a continuation of application No. 17/103,333, filed on Nov. 24, 2020, now Pat. No. 11,290,744, which is a continuation of application No. 16/434,950, filed on Jun. 7, 2019, now Pat. No. 10,880,574, which is a division of application No. 15/963,787, filed on Apr. 26, 2018, now Pat. No. 10,349,082, which is a division of application No. 15/845,690, filed on Dec. 18, 2017, now Pat. No. 10,334,272, which is a continuation of application No. 15/070,832, filed on Mar. 15, 2016, now Pat. No. 9,848,206, which is a continuation of application No. 14/256,059, filed on Apr. 18, 2014, now Pat. No. 9,319,683, which is a continuation of application No. PCT/KR2012/008442, filed on Oct. 16, 2012.
- (60) Provisional application No. 61/557,385, filed on Nov. 8, 2011, provisional application No. 61/548,706, filed on Oct. 18, 2011.

Publication Classification

(51) Int. Cl.

H04N 19/593 (2006.01)H04N 19/426 (2006.01)H04N 19/176 (2006.01)

H04N 19/11	(2006.01)
H04N 19/463	(2006.01)
H04N 19/117	(2006.01)
H04N 19/122	(2006.01)
H04N 19/124	(2006.01)
H04N 19/129	(2006.01)
H04N 19/13	(2006.01)
H04N 19/159	(2006.01)
H04N 19/174	(2006.01)
H04N 19/44	(2006.01)
H04N 19/61	(2006.01)
H04N 19/625	(2006.01)
H04N 19/82	(2006.01)
H04N 19/96	(2006.01)

U.S. Cl. (52)

CPC H04N 19/593 (2014.11); H04N 19/426 (2014.11); H04N 19/176 (2014.11); H04N 19/11 (2014.11); H04N 19/463 (2014.11); H04N 19/117 (2014.11); H04N 19/122 (2014.11); H04N 19/124 (2014.11); H04N 19/129 (2014.11); H04N 19/13 (2014.11); H04N 19/159 (2014.11); H04N 19/174 (2014.11); H04N 19/44 (2014.11); H04N 19/61 (2014.11): H04N 19/625 (2014.11): H04N 19/82 (2014.11); H04N 19/96 (2014.11)

ABSTRACT (57)

A method for intra prediction comprises determining a first MPM candidate corresponding to a left-side candidate block on the basis of a position of the left-side candidate block adjacent to a left side of a current block; determining a second MPM candidate corresponding to an upper-end candidate block on the basis of a position of the upper-end candidate block adjacent to an upper end of the current block; generating an MPM candidate list including a plurality of MPM candidates, on the basis of the first MPM candidate and the second MPM candidate; and determining one MPM candidate of the pluraity of the MPM candidates that constitute the MPM candidate list as an intra prediction mode of the current block, and performing intra prediction for the current block on the basis of the determined intra prediction mode to generate a prediction block corresponding to the current block.

