

(19) United States

(12) Patent Application Publication (10) Pub. No.: US 2024/0215361 A1 JEONG et al.

Jun. 27, 2024 (43) **Pub. Date:**

(54) **DISPLAY DEVICE**

(71) Applicant: LG DISPLAY CO., LTD., Seoul (KR)

(72) Inventors: **HoYoung JEONG**, Gyeonggi-do (KR);

Harkjin KIM, Incheon (KR)

Assignee: LG DISPLAY CO., LTD., Seoul (KR)

(21) Appl. No.: 18/601,140

(22) Filed: Mar. 11, 2024

Related U.S. Application Data

(63) Continuation of application No. 18/174,406, filed on Feb. 24, 2023, now Pat. No. 11,963,414, which is a continuation of application No. 17/110,146, filed on Dec. 2, 2020, now Pat. No. 11,616,114.

(30)Foreign Application Priority Data

(KR) 10-2019-0158908 Dec. 3, 2019

Publication Classification

(51) Int. Cl. H10K 59/131 (2006.01)G06F 3/041 (2006.01)

G06F 3/044	(2006.01)
G06V 40/13	(2006.01)
H04N 23/57	(2006.01)
H10K 59/126	(2006.01)
H10K 59/40	(2006.01)

(52) U.S. Cl.

CPC H10K 59/131 (2023.02); G06F 3/0412 (2013.01); G06F 3/04164 (2019.05); H04N 23/57 (2023.01); H10K 59/126 (2023.02); G06F 3/0446 (2019.05); G06F 2203/04111 (2013.01); G06V 40/1306 (2022.01); H10K 59/40 (2023.02)

(57)ABSTRACT

A display device includes a display panel including a display area on which an image is displayed, a substrate, and an electrode located over the substrate and disposed in the display area; and a camera photographing a front of the display panel without being exposed to the front surface of the display panel, being disposed under the display area of the display panel, and overlapping with a first area in the display area, wherein the electrode overlaps with the first area, and wherein the electrode comprises a semi-transmissive layer positioned over the substrate, an optical path compensation layer positioned on the semi-transmissive layer, and a metal layer positioned on the optical path compensation layer.

10

