



(10) Pub. No.: US 2024/0237486 A9
(48) Pub. Date: Jul. 11, 2024
CORRECTED PUBLICATION

H10K 59/121 (2006.01)

H10K 59/122 (2006.01)

H10K 59/131 (2006.01)

H10K 71/20 (2006.01)

(52) U.S. Cl.

CPC ***H10K 59/873*** (2023.02); ***H10K 59/1201***
(2023.02); ***H10K 59/1213*** (2023.02); ***H10K***
59/122 (2023.02); ***H10K 59/131*** (2023.02);
H10K 71/231 (2023.02)

(72) Inventors: **Woo Yong SUNG**, Yongin-si (KR);
Seung Yong SONG, Yongin-si (KR);
Jeong Seok LEE, Yongin-si (KR)

(21) Appl. No.: 18/224,734

(22) Filed: **Jul. 21, 2023**

(57) **ABSTRACT**

Prior Publication Data

(15) Correction of US 2024/0138234 A1 Apr. 25, 2024
See (22) Filed.
See (30) Foreign Application Priority Data.

(65) US 2024/0138234 A1 Apr. 25, 2024

(30) **Foreign Application Priority Data**

Oct. 21, 2022 (KR) 10-2022-0136080

Publication Classification

(51) **Int. Cl.**
H10K 59/80 (2006.01)
H10K 59/12 (2006.01)

A display device includes a substrate including a display area and a non-display area; a light-emitting array layer; an encapsulation structure; pads disposed in a pad area which is a part of the non-display area on the substrate; a dam structure disposed in the non-display area on the substrate and surrounding an edge of the display area; an encapsulation auxiliary structure corresponding to another part of the non-display area except the pad area, surrounding a part of an edge of the display area, and disposed between the dam structure and an edge of the substrate; and a first multilayer disposed between the substrate and each of the dam structure and the encapsulation auxiliary structure, and including an undercut structure by two or more different metal materials which are stacked.

