

(19) **United States**

(12) **Patent Application Publication**
Bhatt et al.

(10) **Pub. No.: US 2023/0230718 A1**

(43) **Pub. Date: Jul. 20, 2023**

(54) **INTERMITTENT TAPE**

(52) **U.S. Cl.**

(71) Applicant: **Sterlite Technologies Limited,**
Gurugram (IN)

CPC **H01B 5/14** (2013.01); **H01B 11/1869**
(2013.01)

(72) Inventors: **Darshana Bhatt,** Gurugram (IN);
Gourav Kumar, Gurugram (IN)

(57) **ABSTRACT**

(73) Assignee: **Sterlite Technologies Limited,**
Gurugram (IN)

(21) Appl. No.: **17/705,243**

(22) Filed: **Mar. 25, 2022**

(30) **Foreign Application Priority Data**

Dec. 30, 2020 (IN) 202011057136

Publication Classification

(51) **Int. Cl.**
H01B 5/14 (2006.01)

The present disclosure provides an intermittent tape (100) disposed of around a pair of conductors. The intermittent tape (100) has a top dielectric layer (102), a bottom dielectric layer (106) and a conductive layer (104). The conductive layer (104) is sandwiched between the top dielectric layer (102) and the bottom dielectric layer (106). The conductive layer (104) includes conductive segments (108) and non-conductive segments (110). The non-conductive segments (110) are defined by an absence of the conductive segments (108). The conductive segments (108) and the non-conductive segments (110) are arranged alternately. A width of the non-conductive segments (110) between the conductive segments (108) is constant.

