



US 20240244860A1

(19) **United States**

(12) **Patent Application Publication**
SAKUMA et al.

(10) **Pub. No.: US 2024/0244860 A1**

(43) **Pub. Date: Jul. 18, 2024**

(54) **LIGHT EMITTING ELEMENT AND AMINE COMPOUND FOR THE SAME**

H10K 50/15 (2023.01)

H10K 50/16 (2023.01)

H10K 85/60 (2023.01)

(71) Applicant: **Samsung Display Co., Ltd.**, Yongin-si (KR)

(52) **U.S. Cl.**

CPC *H10K 50/11* (2023.02); *C09K 11/06*

(2013.01); *H10K 50/15* (2023.02); *H10K*

50/16 (2023.02); *H10K 85/633* (2023.02);

C09K 2211/1018 (2013.01)

(72) Inventors: **Takao SAKUMA**, Yokohama (JP);
XiuLan JIN, Yokohama (JP); **Ichinori TAKADA**, Yokohama (JP)

(21) Appl. No.: **18/532,924**

(22) Filed: **Dec. 7, 2023**

(30) **Foreign Application Priority Data**

Dec. 23, 2022 (KR) 10-2022-0182966

Publication Classification

(51) **Int. Cl.**

H10K 50/11 (2023.01)

C09K 11/06 (2006.01)

(57)

ABSTRACT

A light emitting element and an amine compound for a light emitting element is provided. The light emitting element includes a first electrode, a second electrode on the first electrode, and at least one functional layer (e.g., hole transport layer) between the first electrode and the second electrode. The functional layer includes a tertiary amine compound represented by a specific chemical structure (i.e., Formula 1). The tertiary amine compound is configured so that the hole transport properties of the functional layer (e.g., hole transport layer) and the emission efficiency and lifetime of the light emitting element may be enhanced or improved.

