



US 20240237459A1

(19) **United States**

(12) **Patent Application Publication**
Jang et al.

(10) **Pub. No.: US 2024/0237459 A1**

(43) **Pub. Date: Jul. 11, 2024**

(54) **DISPLAY APPARATUS**

Publication Classification

(71) Applicant: **Samsung Display Co., Ltd.**, Yongin-si (KR)

(72) Inventors: **Kyeongwoo Jang**, Yongin-si (KR); **Sewan Son**, Yongin-si (KR); **Jiseon Lee**, Yongin-si (KR); **Kwanhee Lee**, Yongin-si (KR); **Seunghyun Lee**, Yongin-si (KR); **Sugwoo Jung**, Yongin-si (KR)

(51) **Int. Cl.**
H10K 59/35 (2006.01)
H10K 59/122 (2006.01)
H10K 59/123 (2006.01)
H10K 59/131 (2006.01)
(52) **U.S. Cl.**
CPC **H10K 59/353** (2023.02); **H10K 59/122** (2023.02); **H10K 59/123** (2023.02); **H10K 59/131** (2023.02)

(21) Appl. No.: **18/398,318**

(22) Filed: **Dec. 28, 2023**

(30) **Foreign Application Priority Data**

Jan. 5, 2023 (KR) 10-2023-0001946

(57) **ABSTRACT**

A display apparatus including a substrate, a first sub-pixel electrode disposed over the substrate, a metal bank layer overlapping the first sub-pixel electrode, an inorganic bank layer disposed on the first sub-pixel electrode and disposed under the metal bank layer, and an auxiliary electrode overlapping the metal bank layer in the non-sub-pixel area, wherein a bottom surface of the inorganic bank layer is in contact with the auxiliary electrode through a first contact hole.

