

(19) United States

(12) Patent Application Publication (10) Pub. No.: US 2023/0231130 A1

Jul. 20, 2023 (43) **Pub. Date:**

(54) POSITIVE ELECTRODE SLURRY COMPOSITION, POSITIVE ELECTRODE PLATE COMPRISING SAME, SECONDARY BATTERY, BATTERY MODULE, BATTERY PACK AND POWER CONSUMING DEVICE

(71) Applicant: CONTEMPORARY AMPEREX TECHNOLOGY CO., LIMITED,

Ningde (CN)

(72) Inventor: **Haotian XIE**, Ningde (CN)

Assignee: **CONTEMPORARY AMPEREX** TECHNOLOGY CO., LIMITED,

Ningde (CN)

(21) Appl. No.: 18/119,382

(22) Filed: Mar. 9, 2023

Related U.S. Application Data

(63) Continuation of application No. PCT/CN2021/ 134474, filed on Nov. 30, 2021.

Publication Classification

(51) Int. Cl. H01M 4/58 (2006.01)H01M 4/62 (2006.01)H01M 10/0525 (2006.01)H01M 50/204 (2006.01)

(52) U.S. Cl. CPC H01M 4/5825 (2013.01); H01M 4/623 (2013.01); H01M 4/624 (2013.01); H01M 10/0525 (2013.01); H01M 50/204 (2021.01); H01M 2004/021 (2013.01)

(57)ABSTRACT

A positive electrode slurry composition of the present application may comprise a positive electrode active material, a lithium-supplementing agent and a binder, wherein

the positive electrode active material may include a lithium-containing phosphate represented by formula

$$\text{LiFe}_{1-b1-c1}\text{Mn}_{b1}\text{M}^{1}_{c1}\text{PO}_{4}$$
 formula (I)

in which $0 \le b1 \le 1$, $0 \le c1 \le 0.1$, and M¹ is selected from at least one of transition metal elements and non-transition metal elements in addition to Fe and Mn;

the lithium-supplementing agent may be selected from one or more of lithium metal oxides of Li_{al}M²O_{0.5(2+} a_1), $\text{Li}_2\text{M}^3\text{O}_3$, $\text{Li}_2\text{M}^4\text{O}_4$, $\text{Li}_3\text{M}^5\text{O}_4$, $\text{Li}_5\text{M}^6\text{O}_4$, and $\text{Li}_5\text{M}^7\text{O}_6$, and

the binder may be represented by formula (II):

formula (II)

$$R_1 - \underbrace{\begin{bmatrix} F & F & F & F & F & H & F \\ C & C & x & C & C & y & C & C \\ F & F & H & F & H & F \end{bmatrix}}_{x} \underbrace{\begin{bmatrix} F & F & H & F \\ C & y & C & C & y \\ F & F & H & F & H & F \end{bmatrix}}_{z} R_2$$

in which R₁ and R₂ are independently H or F, x, y, and z are all positive integers, and 0.52≤(4x+3y+2z)/(4x+4y+ 4z)≤0.7.



