



US 20220354033A1

(19) **United States**

(12) **Patent Application Publication**

Powell, JR. et al.

(10) **Pub. No.: US 2022/0354033 A1**

(43) **Pub. Date: Nov. 3, 2022**

(54) **FERRITE SHIELD LOCATED
INTERMEDIATE A WIRELESS POWER
TRANSMITTER AND RECEIVER AND
METHOD OF USING SAME**

(71) Applicant: **Aptiv Technologies Limited**, St.
Michael (BB)

(72) Inventors: **George Powell, JR.**, Cortland, OH
(US); **James Cook**, Poland, OH (US)

(21) Appl. No.: **17/732,441**

(22) Filed: **Apr. 28, 2022**

Related U.S. Application Data

(60) Provisional application No. 63/181,938, filed on Apr.
29, 2021.

Publication Classification

(51) **Int. Cl.**
H05K 9/00 (2006.01)
H02J 50/00 (2006.01)
H02J 50/10 (2006.01)
(52) **U.S. Cl.**
CPC *H05K 9/0088* (2013.01); *H02J 50/005*
(2020.01); *H02J 50/10* (2016.02)

(57) **ABSTRACT**

An adapter device is configured to interface between a wireless power receiver that includes a first array of magnets arranged around a receiver coil in the wireless power receiver and a wireless power transmitter lacking a corresponding array of magnets arranged around a source coil in the wireless power transmitter. The adapter device includes a substrate and a ferrite shield formed of a magnetic material and configured to be placed between the wireless power receiver and the wireless power transmitter.

