

(19) United States

(12) Patent Application Publication NAKAO et al.

(10) Pub. No.: US 2024/0235267 A9

Jul. 11, 2024 (48) **Pub. Date:** CORRECTED PUBLICATION

(54) CONTACTLESS POWER FEED APPARATUS AND POWER TRANSMISSION METHOD

(71) Applicant: **OMRON Corporation**, KYOTO (JP)

Inventors: Goro NAKAO, KYOTO (JP); Yuki ITO, KYOTO (JP); Taichi MISHIMA,

KYOTO (JP)

Assignee: **OMRON Corporation**, KYOTO (JP)

(21) Appl. No.: 18/464,246

(22) Filed: Sep. 10, 2023

Prior Publication Data

Correction of US 2024/0136860 A1 Apr. 25, 2024 (15)See (22) Filed See (30) Foreign Application Data

(65) US 2024/0136860 A1 Apr. 25, 2024

(30)Foreign Application Priority Data

Oct. 19, 2022 (JP) 2022-167894

Publication Classification

(51) **Int. Cl.**

H02J 50/12 (2006.01)H02J 50/80 (2006.01)

H02M 1/00

H02M 3/00

(2006.01)(2006.01)

U.S. Cl.

CPC H02J 50/12 (2016.02); H02J 50/80 (2016.02); H02M 1/0054 (2021.05); H02M

3/01 (2021.05)

(57)ABSTRACT

A power reception device 3 includes: an estimation circuit 28 estimating a load resistance of an entire contactless power feed apparatus 1; and a reception-side communicator 27 transmitting an estimated value of the load resistance of the entire contactless power feed apparatus 1 to a power transmission device 2. The power transmission device 2 has a power supply circuit 11 supplying AC power to a transmission coil 12 supplying power to the power reception device 3. The power transmission device 2 further includes a control circuit 18 decreasing an input/output gain of a transmission-side DC-DC converter 31 included in the power supply circuit 11 by a predetermined amount when the estimated value of the load resistance is less than a predetermined allowed lower limit, and maintaining or increasing the input/output gain when the estimated value of the load resistance is equal to or greater than the predetermined allowed lower limit.



