



US 20240179840A1

(19) **United States**

(12) **Patent Application Publication**  
**HIRATA et al.**

(10) **Pub. No.: US 2024/0179840 A1**

(43) **Pub. Date: May 30, 2024**

(54) **FLEXIBLE PRINTED BOARD AND  
FLEXIBLE PRINTED BOARD CONNECTION  
STRUCTURE**

(71) Applicant: **NIPPON MEKTRON, LTD.**, Tokyo  
(JP)

(72) Inventors: **Masanori HIRATA**, Tokyo (JP); **Garō  
MIYAMOTO**, Tokyo (JP); **Shunsuke  
AOYAMA**, Tokyo (JP)

(73) Assignee: **NIPPON MEKTRON, LTD.**, Tokyo  
(JP)

(21) Appl. No.: **18/481,201**

(22) Filed: **Oct. 4, 2023**

(30) **Foreign Application Priority Data**

Nov. 29, 2022 (JP) ..... 2022-190416

**Publication Classification**

(51) **Int. Cl.**  
**H05K 1/11** (2006.01)  
**H05K 1/02** (2006.01)  
**H05K 1/03** (2006.01)  
(52) **U.S. Cl.**  
CPC ..... **H05K 1/118** (2013.01); **H05K 1/0298**  
(2013.01); **H05K 1/0393** (2013.01); **H05K**  
**2201/0154** (2013.01)

(57)

**ABSTRACT**

Provided is a flexible printed board including: an insulating base material; a plurality of first wiring lines disposed on a front surface side of the base material; a plurality of first terminals each provided on an external connection side, of a respective one of the plurality of first wiring lines; a plurality of second wiring lines disposed on a rear surface side of the base material; and a plurality of second terminals each provided on an external connection side, of a respective one of the plurality of second wiring lines; in which: a restraining space for restraining surface flashover is provided from a first outermost terminal, which is outermost of the plurality of first terminals, through an edge portion of the base material, to a second outermost terminal, which is outermost of the plurality of second terminals.

