

(19) United States

(12) Patent Application Publication (10) Pub. No.: US 2023/0231473 A1 CHO et al.

Jul. 20, 2023 (43) Pub. Date:

(54) SWITCHING REGULATOR, SYSTEM-ON-CHIP INCLUDING THE SWITCHING REGULATOR, AND OPERATING METHOD OF THE SWITCHING REGULATOR

(71) Applicant: Samsung Electronics Co., Ltd., Suwon-

si (KR)

Inventors: Jeong Hyun CHO, Daejeon (KR); Hyun Sik KIM, Daejeon (KR); Hong Hyun

BAE, Daejeon (KR)

Assignees: Samsung Electronics Co., Ltd., Suwon-

si (KR); KOREA ADVANCED INSTITUTE OF SCIENCE AND TECHNOLOGY, Daejeon (KR)

Appl. No.: 18/065,164

Filed: (22)Dec. 13, 2022

(30)Foreign Application Priority Data

Jan. 19, 2022 (KR) 10-2022-0008045 (KR) 10-2022-0092373 Jul. 26, 2022

Publication Classification

(51) Int. Cl. H02M 3/07 (2006.01)(2006.01) H02M 1/00 G06F 1/26 (2006.01)

(52) U.S. Cl. CPC H02M 3/07 (2013.01); G06F 1/26 (2013.01); H02M 1/0009 (2021.05)

(57)**ABSTRACT**

A switching regulator, system-on-chip including the switching regulator, and operating method of the switching regulator are provided. The switching regulator comprises a first inductor having a first end connected to a first node and a second end connected to an output terminal, a second inductor having a first end connected to a second node and a second end connected to the output terminal, a flying capacitor having a first end connected to the first node and a second end connected to the second node, and control circuitry configured to at each of first through fourth times control the first switch, the second switch, the third switch, the fourth switch, the fifth switch, the sixth switch, the seventh switch, and the eighth switch to cause the flying capacitor to store a voltage corresponding to a difference between currents flowing in the first inductor and the second inductor.

