



US 20240213477A1

(19) **United States**

(12) **Patent Application Publication**  
**KO et al.**

(10) **Pub. No.: US 2024/0213477 A1**

(43) **Pub. Date: Jun. 27, 2024**

(54) **ANODE COMPOSITION, LITHIUM  
SECONDARY BATTERY ANODE  
COMPRISING SAME, AND LITHIUM  
SECONDARY BATTERY COMPRISING  
ANODE**

**Publication Classification**

(51) **Int. Cl.**

**H01M 4/62** (2006.01)

**H01M 4/02** (2006.01)

**H01M 4/48** (2006.01)

(52) **U.S. Cl.**

CPC ..... **H01M 4/622** (2013.01); **H01M 4/48**

(2013.01); **H01M 2004/021** (2013.01); **H01M**

**2004/027** (2013.01); **H01M 2220/30** (2013.01)

(71) Applicant: **LG ENERGY SOLUTION, LTD.,**  
Seoul (KR)

(72) Inventors: **Minjin KO**, Daejeon (KR); **Chan Soo  
JUN**, Daejeon (KR)

(73) Assignee: **LG ENERGY SOLUTION, LTD.,**  
Seoul (KR)

(57)

**ABSTRACT**

(21) Appl. No.: **18/288,003**

(22) PCT Filed: **Dec. 14, 2022**

(86) PCT No.: **PCT/KR2022/020353**

§ 371 (c)(1),

(2) Date: **Oct. 23, 2023**

(30) **Foreign Application Priority Data**

Dec. 15, 2021 (KR) ..... 10-2021-0180142

A negative electrode composition, a negative electrode for a lithium secondary battery including the same, and a lithium secondary battery including a negative electrode are disclosed. The negative electrode composition including a negative electrode binder comprising a graphene oxide and at least one water-soluble macromolecular polymer; a negative electrode active material; and a negative electrode conductive material, wherein the graphene oxide has a lateral size of 0.3  $\mu\text{m}$  or greater and 20  $\mu\text{m}$  or less, and wherein the graphene oxide has a ratio of carbon (C)/oxygen (O) of 0.5 or greater and 3.5 or less.

