US 20220368123A1

(19) **United States**

(12) **Patent Application Publication**

(10) **Pub. No.: US 2022/0368123 A1**

(43) **Pub. Date: Nov. 17, 2022**

van Besouw et al.

(54) **DISCONNECTOR DEVICE AND OVERVOLTAGE PROTECTION ASSEMBLY INCLUDING THE SAME**

(71) Applicant: **Hubbell Incorporated**, Shelton, CT (US)

(72) Inventors: **Bastiaan Hubertus van Besouw**, Strongsville, OH (US); **Peter James Swales**, Aiken, SC (US); **Sidharth Suresh Iyer**, Wadsworth, OH (US); **Mohamed Fayaz Suleiman Khatri**, Macedonia, OH (US); **Stephen Franklin Poterala**, Aiken, SC (US); **Robert Christopher Schmitt**, Lexington, SC (US); **Xingniu Huo**, Medina, OH (US)

(21) Appl. No.: **17/871,729**

(22) Filed: **Jul. 22, 2022**

Related U.S. Application Data

(63) Continuation of application No. 16/862,052, filed on Apr. 29, 2020, now Pat. No. 11,411,386.

(60) Provisional application No. 62/840,086, filed on Apr. 29, 2019, provisional application No. 62/933,649, filed on Nov. 11, 2019, provisional application No. 62/990,006, filed on Mar. 16, 2020.

Publication Classification

(51) **Int. Cl.**

H02H 3/20 (2006.01)

H02H 3/02 (2006.01)

(52) **U.S. Cl.**

CPC ***H02H 3/20*** (2013.01); ***H02H 3/021*** (2013.01); ***H02H 3/02*** (2013.01); *H02G 13/80* (2013.01)

(57) **ABSTRACT**

A disconnector device including an isolator connected between a first terminal and to a second terminal, and a sleeve positioned around the isolator and moveable between an un-extended position prior to the isolator operating and an extended position after the isolator operates, the sleeve being configured to trap debris produced by operation of the isolator.