



US 20240214160A1

(19) **United States**

(12) **Patent Application Publication**
GAO

(10) **Pub. No.: US 2024/0214160 A1**

(43) **Pub. Date: Jun. 27, 2024**

(54) **CARRIER SWITCHING TRANSMISSION
METHOD AND APPARATUS, AND
TERMINAL AND NETWORK-SIDE-DEVICE**

Publication Classification

(71) Applicant: **DATANG MOBILE
COMMUNICATIONS EQUIPMENT
CO., LTD.**, Beijing (CN)

(51) **Int. Cl.**
H04L 5/00 (2006.01)
H04W 72/1268 (2006.01)
H04W 72/21 (2006.01)
(52) **U.S. Cl.**
CPC **H04L 5/0053** (2013.01); **H04L 5/0094**
(2013.01); **H04W 72/1268** (2013.01); **H04W**
72/21 (2023.01)

(72) Inventor: **Xuejuan GAO**, Beijing (CN)

(73) Assignee: **DATANG MOBILE
COMMUNICATIONS EQUIPMENT
CO., LTD.**, Beijing (CN)

(57) **ABSTRACT**

(21) Appl. No.: **18/555,635**

(22) PCT Filed: **Mar. 14, 2022**

(86) PCT No.: **PCT/CN2022/080615**

§ 371 (c)(1),

(2) Date: **Oct. 16, 2023**

(30) **Foreign Application Priority Data**

Apr. 16, 2021 (CN) 202110414398.3

A carrier switching transmission method and apparatus, and a terminal and a network-side device are provided. The method includes: when a plurality of physical uplink control channels PUCCHs transmitted on a first carrier needs to do carrier switching and all of the plurality of PUCCHs are determined to be transmitted in a first time unit on a second carrier after the carrier switching, sending by a terminal one or more PUCCHs in the first time unit on the second carrier according to a first rule after the carrier switching, wherein the plurality of PUCCHs does not overlap in a time domain on the first carrier. PUCCH transmission may be implemented through PUCCH carrier switching.

When a plurality of physical uplink control channels (PUCCHs) transmitted on a first carrier needs to do carrier switching, and each of the plurality of PUCCHs is determined to be transmitted in a first time unit on a second carrier after the carrier switching, sending PUCCHs in the first time unit on the second carrier by the terminal according to a first rule after the carrier switching , wherein the plurality of PUCCHs does not overlap in a time domain on the first carrier.

101