

(19) United States

(12) Patent Application Publication (10) Pub. No.: US 2024/0213280 A1 KIM et al.

Jun. 27, 2024 (43) Pub. Date:

(54) IMAGE SENSOR

(71) Applicant: Samsung Electronics Co., Ltd., Suwon-si (KR)

(72) Inventors: Jae Hong KIM, Suwon-si (KR); Dae Hwa PAIK, Seoul (KR); Seung Hyun LIM, Hwaseong-si (KR); Sin Hwan

LIM, Hwaseong-si (KR)

(73) Assignee: Samsung Electronics Co., Ltd.,

Suwon-si (KR)

(21)Appl. No.: 18/599,687

(22)Filed: Mar. 8, 2024

Related U.S. Application Data

(63) Continuation of application No. 17/502,499, filed on Oct. 15, 2021, which is a continuation of application No. 16/354,593, filed on Mar. 15, 2019, now Pat. No. 11,152,407.

(30)Foreign Application Priority Data

Aug. 16, 2018 (KR) 10-2018-0095358

Publication Classification

(51)Int. Cl. H01L 27/146 (2006.01)H04N 25/75 (2006.01)H04N 25/767 (2006.01)H04N 25/778 (2006.01) H04N 25/78 (2006.01)

U.S. Cl. (52)

CPC .. H01L 27/14609 (2013.01); H01L 27/14603 (2013.01); H04N 25/75 (2023.01); H04N 25/767 (2023.01); H04N 25/778 (2023.01); H04N 25/78 (2023.01)

(57)**ABSTRACT**

An image sensor includes a first column line and a second column line configured to extend in a first direction, a plurality of pixel groups configured to connect to the first column line or the second column line and to comprise a plurality of pixels in each of the plurality of pixel groups, a bias circuit configured to comprise a first current circuit and a second current circuit configured to output different bias currents in a first operational mode, and a switching circuit configured to connect the first column line to the first current circuit and connect the second column line to the second current circuit during a first time period, and to connect the first column line to the second current circuit and connect the second column line to the first current circuit during a second time period subsequent to the first time period in the first operational mode.

1

