



US 20240235515A9

(19) **United States**
(12) **Patent Application Publication**
KIKUDA

(10) **Pub. No.: US 2024/0235515 A9**
(48) **Pub. Date: Jul. 11, 2024**
CORRECTED PUBLICATION

(54) **FILTER DEVICE AND RADIO FREQUENCY FRONT END CIRCUIT**

Publication Classification

(71) Applicant: **Murata Manufacturing Co., Ltd.**,
Nagaokakyo-shi (JP)

(72) Inventor: **Masayuki KIKUDA**, Nagaokakyo-shi
(JP)

(21) Appl. No.: **18/530,295**

(22) Filed: **Dec. 6, 2023**

Prior Publication Data

(15) Correction of US 2024/0136995 A1 Apr. 25, 2024
See (30) Foreign Application Priority Data.

(65) US 2024/0136995 A1 Apr. 25, 2024

Related U.S. Application Data

(63) Continuation of application No. PCT/JP2022/
022348, filed on Jun. 1, 2022.

(30) **Foreign Application Priority Data**

Jul. 6, 2021 (JP) 2021-112053

(51) **Int. Cl.**
H03H 7/01 (2006.01)
H01F 27/28 (2006.01)
H01F 27/40 (2006.01)
H01G 4/30 (2006.01)
H01G 4/40 (2006.01)
(52) **U.S. Cl.**
CPC **H03H 7/0115** (2013.01); **H01F 27/2804**
(2013.01); **H01F 27/40** (2013.01); **H01G 4/30**
(2013.01); **H01G 4/40** (2013.01)

(57) **ABSTRACT**

A filter device includes input and output terminals, first and second ground electrodes opposed to each other, and a resonator connected to one of the input and output terminals. The resonator includes a third ground electrode, and first, second, and third resonant portions. The third ground electrode is between and connected to the first and second ground electrodes. The first resonant portion is between the first and third ground electrodes, and connected to the third ground electrode and one of the input and output terminals. The second resonant portion is between the first and third ground electrodes, and connected to the third ground electrode. The third resonant portion is between the second and third ground electrodes, and connected to the third ground electrode.

