



US 20220368290A1

(19) **United States**

(12) **Patent Application Publication**
Faulstich

(10) **Pub. No.: US 2022/0368290 A1**

(43) **Pub. Date: Nov. 17, 2022**

(54) **POWER LIMITER CONFIGURATION FOR AUDIO SIGNALS**

(71) Applicant: **Biamp Systems, LLC**, Beaverton, OR (US)

(72) Inventor: **Aaron Faulstich**, Beaverton, OR (US)

(73) Assignee: **Biamp Systems, LLC**, Beaverton, OR (US)

(21) Appl. No.: **17/874,186**

(22) Filed: **Jul. 26, 2022**

H03G 3/30 (2006.01)

H04R 3/02 (2006.01)

H04R 3/04 (2006.01)

G10L 25/21 (2006.01)

H03G 11/00 (2006.01)

(52) **U.S. Cl.**

CPC **H03F 1/3264** (2013.01); **H04R 3/007**

(2013.01); **H03G 3/3005** (2013.01); **H04R**

3/02 (2013.01); **H04R 3/04** (2013.01); **G10L**

25/21 (2013.01); **H03G 11/008** (2013.01);

H03G 2201/106 (2013.01)

Related U.S. Application Data

(63) Continuation of application No. 17/087,658, filed on Nov. 3, 2020, now Pat. No. 11,398,801, which is a continuation of application No. 16/721,654, filed on Dec. 19, 2019, now Pat. No. 10,826,441.

(60) Provisional application No. 62/800,807, filed on Feb. 4, 2019.

Publication Classification

(51) **Int. Cl.**

H03F 1/32 (2006.01)

H04R 3/00 (2006.01)

(57)

ABSTRACT

Example embodiments provide a process that includes one or more of receiving an audio signal at a feedback compressor circuit, determining how much to attenuate the audio signal when a power level of the audio signal exceeds a threshold power level, combining the audio signal with an auxiliary attenuation signal from an auxiliary attenuation source and a compressed attenuation signal from the feedback compressor circuit to create a combination signal, and generating an audio output signal of the feedback compressor circuit based on the combination signal.

300

