



US 20240235314A9

(19) **United States**
(12) **Patent Application Publication**
WANG et al.

(10) **Pub. No.: US 2024/0235314 A9**
(48) **Pub. Date: Jul. 11, 2024**
CORRECTED PUBLICATION

(54) **MOTOR AND MOTOR ASSEMBLING METHOD**

Publication Classification

(71) Applicant: **NIDEC CORPORATION**, Kyoto (JP)

(72) Inventors: **Yu WANG**, DALIAN CITY (CN);
Keisuke YOSHINO, Kyoto (JP);
Yonggang YANG, DALIAN CITY (CN); **Masashi OMI**, Kyoto (JP)

(51) **Int. Cl.**
H02K 5/06 (2006.01)
H02K 5/16 (2006.01)
H02K 15/14 (2006.01)
(52) **U.S. Cl.**
CPC **H02K 5/06** (2013.01); **H02K 5/161** (2013.01); **H02K 15/14** (2013.01)

(73) Assignee: **NIDEC CORPORATION**, Kyoto (JP)

(21) Appl. No.: **18/489,835**

(57) **ABSTRACT**

(22) Filed: **Oct. 18, 2023**

Prior Publication Data

(15) Correction of US 2024/0136882 A1 Apr. 25, 2024
See (22) Filed.
See (30) Foreign Application Priority Data.

(65) US 2024/0136882 A1 Apr. 25, 2024

Foreign Application Priority Data

Oct. 20, 2022 (CN) 202211285757.0

The disclosure provides a motor and a motor assembling method. The motor includes a housing having a bottom and a wall portion extending from an edge of the bottom along an axial direction, and a lid connected to the housing on one side in the axial direction of the bottom of the housing. A surface on the one side in the axial direction of the bottom of the housing has a first connection surface. Housing portions on an inside and an outside in a radial direction of the first connection surface are respectively bent in opposite directions intersecting the first connection surface, which ensures sufficient working space when performing work for connecting the housing and the lid.

1

