



US 20230231494A1

(19) **United States**

(12) **Patent Application Publication**  
**Harrison**

(10) **Pub. No.: US 2023/0231494 A1**

(43) **Pub. Date: Jul. 20, 2023**

(54) **INVERTER**

**Publication Classification**

(71) Applicant: **Energy Research Lab LTD**, London  
(GB)

(72) Inventor: **Lee Harrison**, Wilstead (GB)

(73) Assignee: **Energy Research Lab LTD**, London,  
EN (GB)

(21) Appl. No.: **18/161,403**

(22) Filed: **Jan. 30, 2023**

**Related U.S. Application Data**

(63) Continuation of application No. PCT/GB21/51996,  
filed on Aug. 2, 2021.

**Foreign Application Priority Data**

(30) Jul. 31, 2020 (GB) ..... 2011928.5  
Jul. 31, 2020 (GB) ..... 2011935.0  
Jul. 31, 2020 (GB) ..... 2011969.9

(51) **Int. Cl.**

**H02M 7/48** (2006.01)

**H02M 3/335** (2006.01)

**H02M 3/00** (2006.01)

**H02M 1/42** (2006.01)

**H02M 7/539** (2006.01)

(52) **U.S. Cl.**

CPC ..... **H02M 7/4815** (2021.05); **H02M 3/33571**  
(2021.05); **H02M 3/01** (2021.05); **H02M**  
**1/4208** (2013.01); **H02M 7/539** (2013.01)

(57)

**ABSTRACT**

There is provided a high frequency AC inverter comprising a DC-DC circuit, an output power circuit and a load circuit and a controller, the load circuit comprising a load circuit detector configured to detect the electrical parameters of the load circuit. The output power circuit comprises a DC to AC driver having a variable frequency output, a HFAC driver circuit comprising a resonant network and a transformer coupled to the HFAC driver circuit and the load circuit. The controller is configured to control the output frequency of the DC to AC driver and the output of the DC to DC circuit in response to the detected electrical parameters of the load circuit.

