



US 20240235214A9

(19) **United States**
(12) **Patent Application Publication**
TAKAHASHI

(10) **Pub. No.: US 2024/0235214 A9**
(48) **Pub. Date: Jul. 11, 2024**
CORRECTED PUBLICATION

(54) **EQUALIZATION CONTROL DEVICE FOR BATTERY**

Publication Classification

(71) Applicant: **TOYOTA JIDOSHA KABUSHIKI KAISHA**, Toyota-shi (JP)

(72) Inventor: **Kohei TAKAHASHI**, Toyota-shi (JP)

(73) Assignee: **TOYOTA JIDOSHA KABUSHIKI KAISHA**, Toyota-shi (JP)

(51) **Int. Cl.**

H02J 7/00 (2006.01)

B60L 58/22 (2006.01)

G01R 31/388 (2006.01)

(52) **U.S. Cl.**

CPC **H02J 7/0016** (2013.01); **B60L 58/22**

(2019.02); **G01R 31/388** (2019.01); **H02J**

7/0049 (2020.01)

(21) Appl. No.: **18/448,207**

(57)

ABSTRACT

(22) Filed: **Aug. 11, 2023**

Prior Publication Data

(15) Correction of US 2024/0136826 A1 Apr. 25, 2024
See (22) Filed.

See (30) Foreign Application Priority Data.

(65) US 2024/0136826 A1 Apr. 25, 2024

(30) **Foreign Application Priority Data**

Oct. 21, 2022 (JP) 2022-169124

The control unit includes: when an absolute value of a difference between a full charge capacity of a 1 cell and a full charge capacity of a 2 cell is equal to or larger than a 1 threshold value, equalization is performed so that an absolute value of a difference between a charge rate of a 1 cell and a charge rate of a 2 cell at the time of full charge is less than a 2 threshold value, and when an absolute value of a difference between a voltage of a 1 cell and a voltage of a 2 cell is equal to or larger than a 3 threshold value, equalization is performed so that an absolute value of a difference between a voltage of a 1 cell and a voltage of a 2 cell becomes less than a 3 threshold value.

