US 20220354032A1

(19) **United States**

(12) **Patent Application Publication**

(10) **Pub. No.: US 2022/0354032 A1**

(43) **Pub. Date: Nov. 3, 2022**

Graff et al.

(54) **ORIENTATION OF MAGNETIC FILLERS TO OPTIMIZE FILM PROPERTIES**

(71) Applicant: **3M INNOVATIVE PROPERTIES COMPANY**, St. Paul, MN (US)

(72) Inventors: **Michael S. Graff**, Woodbury, MN (US); **Derek J. Dehn**, Maplewood, MN (US); **Paul T. Hines**, St. Paul, MN (US); **Charles L. Bruzzone**, Woodbury, MN (US); **Bharat R. Acharya**, Woodbury, MN (US); **Ronald D. Jesme**, Plymouth, MN (US); **William J. Kopecky**, Hudson, WI (US); **Jennifer J. Sokol**, Mahtomedi, MN (US); **Sergei A. Manuilov**, Bayport, MN (US)

(21) Appl. No.: **17/607,991**

(22) PCT Filed: **May 8, 2020**

(86) PCT No.: **PCT/IB2020/054388**

§ 371 (c)(1),
(2) Date: **Nov. 1, 2021**

Related U.S. Application Data

(60) Provisional application No. 62/848,245, filed on May 15, 2019.

Publication Classification

(51) **Int. Cl.**
H05K 9/00 (2006.01)
H01F 1/20 (2006.01)

(52) **U.S. Cl.**
CPC ***H05K 9/0075*** (2013.01); ***H01F 1/20*** (2013.01)

(57) **ABSTRACT**

A magnetic shielding film includes opposing first and second major surfaces and a plurality of particles dispersed therebetween, each particle having a magnetic permeability, a thickness H along a thickness direction of the particle, and a longest dimension L along a length direction of the particle orthogonal to the thickness direction, L/H greater than or equal to 2, the particles defining a plurality of voids therebetween, the length directions of at least 60% of the particles oriented within 5.5 degrees of a same orientation direction.