

(19) United States

(12) Patent Application Publication (10) Pub. No.: US 2023/0231250 A1 TAKAHASHI et al.

Jul. 20, 2023 (43) **Pub. Date:**

(54) CELL CASE OF SECONDARY BATTERY AND BATTERY MODULE

(71) Applicant: NIPPON STEEL CORPORATION,

Tokyo (JP)

Inventors: Takehiro TAKAHASHI, Tokyo (JP);

Akinobu KOBAYASHI, Tokyo (JP)

Assignee: NIPPON STEEL CORPORATION,

Tokyo (JP)

Appl. No.: 18/020,407

(22) PCT Filed: Sep. 7, 2021

(86) PCT No.: PCT/JP2021/032898

§ 371 (c)(1),

(2) Date: Feb. 8, 2023

(30)Foreign Application Priority Data

Oct. 16, 2020 (JP) 2020-174868

Publication Classification

(51) Int. Cl.

H01M 50/204 (2006.01)H01M 10/613 (2006.01)

H01M 50/103 (2006.01)(2006.01)H01M 50/15

(52) U.S. Cl.

CPC H01M 50/204 (2021.01); H01M 10/613 (2015.04); H01M 50/103 (2021.01); H01M 50/15 (2021.01)

(57)ABSTRACT

A cell case of a secondary battery comprised of a can body to which a can bottom is double seamed, in which cell case, it is possible to solve the problem of the drop in cooling efficiency due to the presence of a double seam when cooling such a cell case by a cooling device or using a cooling sheet, and a battery module having a plurality of such cell cases are provided. That is, a cell case of a secondary battery having a rectangular tube-shaped can body, a can bottom double seamed to a bottom end of the can body, and a can lid double seamed to a top end of the can body, in which cell case of a secondary battery, an area ratio 51 of part of the can bottom, comprised of a portion 1 between a plane vertical to the can body a distance of 0.5 mm above a bottom end of a double seam of the can body and the can bottom and a plane vertical to the can body a distance of 1.0 mm below the bottom end of the double seam, with respect to a cross-sectional area of the can body at the bottom end of the double seam is 50% or more, and a battery module having a plurality of such cell cases are provided.

