US 20240235486A1

(19) **United States**

(12) **Patent Application Publication** (10) **Pub. No.: US 2024/0235486 A1**

KOGURE et al. (43) **Pub. Date: Jul. 11, 2024**

(54) **TRACKER MODULE AND COMMUNICATION DEVICE**

(71) Applicant: **Murata Manufacturing Co., Ltd.**, Nagaokakyo-shi (JP)

(72) Inventors: **Takeshi KOGURE**, Nagaokakyo-shi (JP); **Tomohide ARAMATA**, Nagaokakyo-shi (JP); **Toshiki MATSUI**, Nagaokakyo-shi (JP); **Yuuki FUKUDA**, Nagaokakyo-shi (JP)

(21) Appl. No.: **18/616,760**

(22) Filed: **Mar. 26, 2024**

Related U.S. Application Data

(63) Continuation of application No. PCT/JP22/35973, filed on Sep. 27, 2022.

(30) **Foreign Application Priority Data**

Sep. 29, 2021 (JP) 2021-159812

Publication Classification

(51) **Int. Cl.**
H03F 1/02 (2006.01)
H03F 3/24 (2006.01)

(52) **U.S. Cl.**
CPC ***H03F 1/0233*** (2013.01); ***H03F 3/245*** (2013.01); *H03F 2200/105* (2013.01); *H03F 2200/451* (2013.01)

(57) **ABSTRACT**

A tracker module is provided that includes a module laminate and an integrated circuit on the module laminate. The integrated circuit includes a switch unit included in an output switch circuit that selectively outputs at least one of multiple discrete voltages based on a first digital control signal. The first digital control signal includes a digital control line/logic signal indicating one of the multiple discrete voltages. The module laminate includes multiple lines and a ground electrode. The lines are connected to the integrated circuit and the first digital control signal flows through the lines. The ground electrode is connected to a ground terminal. In a sectional view of the module laminate, at least part of the lines is disposed between the integrated circuit and a ground electrode. In a plan view of the module laminate, at least part of the lines matches the ground electrode.