



US 20240244902A1

(19) **United States**

(12) **Patent Application Publication**
WEI et al.

(10) **Pub. No.: US 2024/0244902 A1**

(43) **Pub. Date: Jul. 18, 2024**

(54) **DISPLAY MODULE AND DISPLAY DEVICE**

(52) **U.S. Cl.**

(71) Applicants: **Yunnan Invsight Optoelectronics Technology Co., Ltd.**, Kunming, Yunnan (CN); **BOE Technology Group Co., Ltd.**, Beijing (CN)

CPC **H10K 59/131** (2023.02); **H05K 1/028** (2013.01); **H05K 1/189** (2013.01); **H05K 2201/10128** (2013.01)

(72) Inventors: **Junbo WEI**, Beijing (CN); **Shengji YANG**, Beijing (CN); **Pengcheng LU**, Beijing (CN); **Kuanta HUANG**, Beijing (CN); **Yuanlan TIAN**, Beijing (CN)

(57)

ABSTRACT

(21) Appl. No.: **18/016,679**

(22) PCT Filed: **Feb. 28, 2022**

(86) PCT No.: **PCT/CN2022/078238**

§ 371 (c)(1),

(2) Date: **Jan. 18, 2023**

Publication Classification

(51) **Int. Cl.**

H10K 59/131 (2006.01)

H05K 1/02 (2006.01)

H05K 1/18 (2006.01)

A display module includes a display substrate and a flexible circuit board bonding-connected with the display substrate, wherein the flexible circuit board is bent to a side of the display substrate away from a display side; the flexible circuit board includes a bent region and non-bent regions located at both sides of the bent region; the bent region includes a bending axis, the flexible circuit board is bent along the bending axis, the bent region is provided with one or more openings at a position of the bending axis, and the openings are through holes penetrating the flexible circuit board or grooves not penetrating the flexible circuit board; the bent region includes at least one wiring layer, the wiring layer of the bent region includes multiple traces extending to the non-bent regions on both sides of the bent region, and the plurality of traces do not overlap with the openings.

