

(19) United States

(12) Patent Application Publication (10) Pub. No.: US 2024/0251562 A1

Jul. 25, 2024 (43) **Pub. Date:**

(54) SEMICONDUCTOR DEVICE AND METHOD OF MANUFACTURING THE SAME

(71) Applicant: SK hynix Inc., Icheon-si Gyeonggi-do

Inventor: Nam Jae LEE, Cheongju-si Chungcheongbuk-do (KR)

(73) Assignee: SK hynix Inc., Icheon-si Gyeonggi-do (KR)

(21) Appl. No.: 18/624,721

(22) Filed: Apr. 2, 2024

Related U.S. Application Data

Continuation of application No. 17/578,718, filed on Jan. 19, 2022, now Pat. No. 11,980,033, which is a continuation of application No. 16/851,894, filed on Apr. 17, 2020, now Pat. No. 11,264,399, which is a division of application No. 15/914,130, filed on Mar. 7, 2018, now Pat. No. 10,665,601.

(30)Foreign Application Priority Data

Jul. 31, 2017 (KR) 10-2017-0096929

Publication Classification

(51)	Int. Cl.	
` ′	H10B 43/35	(2006.01)
	H01L 21/768	(2006.01)
	H01L 23/522	(2006.01)
	H10B 41/10	(2006.01)
	H10B 41/27	(2006.01)
	H10B 41/35	(2006.01)
	H10B 43/10	(2006.01)
	H10B 43/27	(2006.01)

(52) U.S. Cl.

CPC *H10B 43/35* (2023.02); *H01L 21/76802* (2013.01); H01L 21/76877 (2013.01); H01L 23/5226 (2013.01); H10B 41/10 (2023.02); H10B 41/27 (2023.02); H10B 41/35 (2023.02); H10B 43/27 (2023.02); H10B 43/10 (2023.02)

(57)**ABSTRACT**

A semiconductor device and a method of manufacturing a semiconductor device may be provided. The semiconductor device may include first and second vertical conductive patterns isolated from each other by a first slit. The semiconductor device may include at least one first half conductive pattern extending toward a first region disposed at one side of the first slit from the first vertical conductive pattern. The semiconductor device may include at least one second half conductive pattern extending toward a second region disposed at the other side of the first slit from the second vertical conductive pattern.

