

(19) United States

(12) Patent Application Publication (10) Pub. No.: US 2022/0368140 A1 ONO et al.

Nov. 17, 2022 (43) **Pub. Date:**

CPC H02J 7/0029 (2013.01); B60L 53/16

(2019.02); **B60L 53/60** (2019.02); **B60L 53/18**

31/1245 (2013.01); G01R 31/3835 (2019.01);

(2019.02); H02J 7/00045 (2020.01); H02J 7/02 (2013.01); G01R 31/52 (2020.01); G01R

(54) CHARGING CONTROLLER AND VEHICLE

(71) Applicant: TOYOTA JIDOSHA KABUSHIKI KAISHA, Toyota-shi (JP)

(72) Inventors: Tomoya ONO, Toyota-shi (JP); Toru

ANDO, Obu-shi (JP); Yamato NIWA,

Kariya-shi (JP)

Assignee: TOYOTA JIDOSHA KABUSHIKI

KAISHA, Toyota-shi (JP)

Appl. No.: 17/736,718 (21)

(22)Filed: May 4, 2022

(30)Foreign Application Priority Data

May 11, 2021 (JP) 2021-080477

Publication Classification

(51)	Int. Cl.	
	H02J 7/00	(2006.01)
	B60L 53/16	(2006.01)
	B60L 53/60	(2006.01)
	B60L 53/18	(2006.01)

H02J 7/02	(2006.01)
G01R 31/52	(2006.01)
G01R 31/12	(2006.01)
G01R 31/3835	(2006.01)

H02J 2207/20 (2020.01)

(52) U.S. Cl.

(57)

A charging controller carries out charging control of a power storage mounted on a vehicle. The vehicle includes a DC charging inlet. The charging controller carries out first charging control when a charging cable which is not a prescribed charging cable is connected to the DC charging inlet and carries out second charging control when the prescribed charging cable is connected to the DC charging inlet. For example, a time period for ground fault detection carried out during charging of the power storage is set differently between first charging control and second charging control. Alternatively, a response delay margin of a charging command is set differently between first charging control and second charging control.

ABSTRACT

