



US 20220377944A1

(19) **United States**(12) **Patent Application Publication**
RAJPUT et al.(10) **Pub. No.: US 2022/0377944 A1**(43) **Pub. Date: Nov. 24, 2022**(54) **COOLING SYSTEM, AIR REMOVAL
ATTACHMENT, AIR REMOVAL METHOD,
AND STORAGE MEDIUM**(71) Applicant: **NEC Corporation**, Minato-ku, Tokyo
(JP)(72) Inventors: **Nirmal Singh RAJPUT**, Tokyo (JP);
Masaki CHIBA, Tokyo (JP); **Mahiro**
HACHIYA, Tokyo (JP); **Takafumi**
NATSUMEDA, Tokyo (JP); **Yoshinori**
MIYAMOTO, Tokyo (JP); **Minoru**
YOSHIKAWA, Tokyo (JP)(73) Assignee: **NEC Corporation**, Minato-ku, Tokyo
(JP)(21) Appl. No.: **17/764,293**(22) PCT Filed: **Oct. 2, 2019**(86) PCT No.: **PCT/JP2019/039729**

§ 371 (c)(1),

(2) Date: **Mar. 28, 2022****Publication Classification**(51) **Int. Cl.**
H05K 7/20 (2006.01)
F28D 15/06 (2006.01)
F28D 15/02 (2006.01)
(52) **U.S. Cl.**
CPC **H05K 7/20827** (2013.01); **H05K 7/20381**
(2013.01); **F28D 15/06** (2013.01); **F28D**
15/0266 (2013.01)(57) **ABSTRACT**

The present invention provides an attachment for a server rack cooling system having at least one heat exchange condenser, the attachment includes: a pipe extension configured to connect to a portion of the server rack cooling system at which air and refrigerant are able to be transferred into the attachment from the at least one heat exchange condenser; a valve on the pipe extension configured to allow exhaust to the outside through the pipe extension at an open position and to block exhaust to the outside at a closed position; and an sensor disposed at a position inside of the pipe extension between the at least one heat exchange condenser and the valve and configured to provide a detection signal determined by a presence of fluid at the position of the sensor; wherein, the valve is opened and closed based on the detection signal from the sensor.

