



US 20220407515A1

(19) **United States**

(12) **Patent Application Publication**  
**BRUWER et al.**

(10) **Pub. No.: US 2022/0407515 A1**

(43) **Pub. Date: Dec. 22, 2022**

(54) **ELECTRONIC DEVICE USER INTERFACE**

**Publication Classification**

(71) Applicant: **AZOTEQ HOLDINGS LIMITED**,  
Nicosia (CY)

(51) **Int. Cl.**

**H03K 17/95** (2006.01)

**H03K 17/955** (2006.01)

**H04R 1/10** (2006.01)

**H03K 17/97** (2006.01)

(72) Inventors: **Frederick Johannes BRUWER**, Paarl  
(ZA); **Daniel Barend RADEMEYER**,  
Paarl (ZA); **Landolf THERON**, Paarl  
(ZA)

(52) **U.S. Cl.**

CPC ..... **H03K 17/952** (2013.01); **H03K 17/955**  
(2013.01); **H04R 1/1041** (2013.01); **H03K**  
**17/97** (2013.01); **H03K 2217/94036** (2013.01);  
**H03K 2217/96038** (2013.01)

(21) Appl. No.: **17/770,647**

(22) PCT Filed: **Oct. 21, 2020**

(86) PCT No.: **PCT/ZA2020/050058**

§ 371 (c)(1),

(2) Date: **Apr. 21, 2022**

(57)

**ABSTRACT**

The invention concerns a robust user interface for electronic devices where a single measurement circuit is used to measured inductance values due to user press events through sealable surface, as well as capacitance values due to user proximity and/or touch events, and with both the measured inductance and capacitance values used to determine user input commands.

(30) **Foreign Application Priority Data**

Oct. 22, 2019 (ZA) ..... 2019/06932

May 7, 2020 (ZA) ..... 2020/02508

